

Report No.: WOAH00066969

DESIGN / CRAFT FABRIC CORPORATION

2230 RIDGE DRIVE GLENVIEW, IL 60025 ATTN: MARTHA BOYNTON

APRIL 25, 2014

IDENTIFICATION SUBMITTED BY CLIENT

DESCRIPTION : XANADU

PO# : SA1091

NO. OF SAMPLES : 1

COLORS: S51

FIBER CONTENT : 100% POLYESTER

END USE : CUBICLE CURTAIN





545 E Algonquin Road, Suite F, Arlington Heights, Illinois 60005 Telephone: 847-871-1020 Fax: 847-439-6156







Report No.: WOAH00066969

TEST RESULTS

NFPA 701 – Fire Tests for Flame Propagation of Textiles and Films – Method 1

Washing Conditions: AATCC 96 at 160°F, Tumble Dry Low (x5)

	After-Flame time (s)	Burning time of materials that falls to the bottom of chamber (s)	Weight before exposure (g)	Weight after exposure (g)	% Weight Loss
Specimen 1	0	0	11.2	8.5	24.1
Specimen 2	0	0	11.2	8.4	25.0
Specimen 3	0	0	11.2	9	19.6
Specimen 4	0	0	11.2	10	10.7
Specimen 5	0	0	11.3	9.6	15.0
Specimen 6	0	0	11.2	9.5	15.2
Specimen 7	0	0	11.2	8.7	22.3
Specimen 8	0	0	11.3	9.1	19.5
Specimen 9	0	0	11.2	8.4	25.0
Specimen 10	0	0	11.2	8.6	23.2
Average	0.0	0.0	11.2	9.0	20.0
Standard Deviation	NA	NA	NA	NA	4.9

To pass, a sample shall meet below criteria

- 10.1.1.1 Fragments or residues of specimens that fall to the floor of the test chamber shall not continue to burn for more than an average of 2 seconds per specimen for the sample of 10 specimens.
- 10.1.1.2 The average weight loss of the 10 specimens in a sample shall be 40 percent or less.
- 10.1.1.3 No individual specimen's percent mass loss shall deviate more than 3 standard deviations from the mean for the 10 specimens.
- 10.1.1.4 When a retest is required, no individual specimen's percent mass loss in the second set of specimens shall deviate from the mean value by more than 3 standard deviations calculated for the second set.

Conclusion: The submitted sample **passes** when tested in accordance with NFPA 701, Fire Tests for Flame Propagation of Textiles and Films, Test Method 1.


Intertek Consumer Goods

545 E Algonquin Road, Suite F, Arlington Heights, Illinois 60005

Telephone: 847-871-1020 Fax: 847-439-6156









OR IF YOU HAVE ANY QUESTIONS, PLEASE FEEL FREE TO CALL: CUSTOMER SERVICE DEPARTMENT. INTERTEK CONSUMER GOODS

Edwin Serrano Account Manager Duraisamy Ravichandran Manager, Operations

D. Ran Dandrany.

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct.

Telephone: 847-871-1020 Fax: 847-439-6156



