

"We Test Per Your Request"=

336 WEST FRONT STREET P.O. BOX 4004 BURLINGTON, NORTH CAROLINA 27215 PHONE (336) 227-7710 • FAX (336) 227-1175 www.diversifiedtestinglabs.com

September 9, 2020

HEALTH CARE INTERIORS 1000 W Crosby Rd, Ste 100 Carrollton, TX 75006

Reference: **Laboratory Test Report**

Lab Identification No. 42592

Invoice No. 73831

One (1) fabric sample, identified as SPRINGSCAPE, was received and tested in accordance with the National Fire Protection Association No. 701, "Standard Methods of Fire Tests for Flame Propagation of Textiles and Films, 2019 Edition, (Test 1)". The results are as follows:

Test Results

Specimen Number	Residual Flame (seconds)	Weight Loss (percent)
1	0.0	10.39
2	0.0	13.69
3	0.0	7.66
4	0.0	14.04
5	0.0	11.09
6	0.0	5.09
7	0.0	14.21
8	0.0	2.25
9	0.0	7.67
<u>10</u>	<u>0.0</u>	<u>4.79</u>
AVG	0.0	9.09

The sample submitted meets the minimum requirements of the above standard. The average percent weight loss cannot exceed 40% and the weight loss of individual specimens cannot exceed mean value plus three standard deviations. The average residual flame cannot exceed 2.0 seconds.

If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Brian S. Dement

BSD/mr

